

Quadro Set 3; Quadro Set 5



Load Cell Certifications:



Features:

- NTEP certified load cells from 250lb-20Klb
- OIML certified load cells from 500kg-5t & 1K-10Klb (QS3-S4);
OIML certified load cells from 1Klb-10Klb (QS5-S4);
- CE, RoHS and ExNepsi certified load cells
- Full Scale Output: 2mV/V ± 0.25% (QS3-S4);
3mV/V ± 0.25% (QS5-S4);
- Junction box is equipped with integrated resistor networks
- Cable is coloured in accordance to the ANYLOAD color code

Complete Set:

- 4 pcs x 563YS or 563YS30 Stainless steel single ended shear beam load cells
- 4 pcs x Stainless steel load cell spacers
- 4 pcs x Stainless steel mounting feet AMFS4
- 1 pc x Stainless steel junction box J04ES-FS
- 1 pc x 20m PVC cable

PART NUMBER

QS3-S4		
Load Cell Capacity	Part No.	Weight (kg) Approx.
250kg.....	QS3-S4-250kg	7.6
500kg.....	QS3-S4-500kg	7.6
1t.....	QS3-S4-1t.....	7.6
2t.....	QS3-S4-2t.....	7.6
3t.....	QS3-S4-3t.....	11.4
5t.....	QS3-S4-5t.....	11.4
500lb	QS3-S4-500lb	7.6
1Klb	QS3-S4-1Klb.....	7.6
2.5Klb	QS3-S4-2.5Klb.....	7.6
4Klb	QS3-S4-4Klb.....	7.6
SE5Klb.....	QS3-S4-SE5Klb	7.6
5Klb	QS3-S4-5Klb.....	11.4
10Klb	QS3-S4-10Klb.....	11.4

PART NUMBER

QS5-S4		
Load Cell Capacity	Part No.	Shipping Weight (kg) Approx.
500lb	QS5-GS-S4-500lb	7.6
1Klb	QS5-S4-1Klb.....	7.6
2.5Klb	QS5-S4-2.5Klb.....	7.6
4Klb	QS5-S4-4Klb.....	7.6
SE5Klb.....	QS5-S4-SE5Klb	7.6
5Klb	QS5-S4-5Klb.....	11.4
10Klb	QS5-S4-10Klb.....	11.4